



- Ultra heavy duty central steel core load distribution construction
- US Coast Guard approved inner closed cell rigid urethane buoyancy foam

- Impact absorbing, resilient heat laminated cross-linked polyethylene foam core foam
- Thick, tough filament nylon tire cord reinforced urethane skin

UTILITY CYLINDRICAL BUOYS

BUOY MODEL	BUOYANCY		BUOY		DIAMETER		HEIGHT		WORKING	
	NET		WEIGHT		OVERALL		OVERALL		LOAD	
	LBS	KG	LBS	KG	FT	M	FT	M	LBS	TONS
CB-10	100	45	55	25	1.3	0.4	2	0.6	5,000	2.3
CB-20	200	90	65	29	1.5	0.5	2.5	0.8	5,000	2.3
CB-30	300	136	90	41	1.7	0.5	2.7	0.8	5,000	2.3
CB-50	500	227	130	59	2.0	0.6	2.0	0.6	7,500	3.4
CB-100	1,000	454	200	91	2.4	0.7	4.0	1.2	10,000	4.5
CB-150	1,500	680	240	109	2.7	0.8	5.0	1.5	10,000	4.5
CB-200	2,000	907	440	200	3.1	0.9	5.2	1.6	20,000	9.1
CB-250	2,500	1,134	600	272	3.5	1.1	5.5	1.7	20,000	9.1
CB-300	3,000	1,361	800	363	4.0	1.2	6.0	1.8	20,000	9.1
CB-400	4,000	1,814	970	440	4.5	1.4	6.2	1.9	40,000	18.0
CB-500	5,000	2,268	1,320	599	4.7	1.5	6.2	1.9	40,000	18.0
CB-600	6,000	2,722	1,740	789	5.0	1.6	6.6	2.0	40,000	18.0

* ACTUAL VALUES FOR ABOVE SIZES MAY VARY +/- 15% DUE TO VARIATIONS IN MATERIALS, TEMPERATURES AND TOLERANCES.