

Pendant Buoys



- Ultra heavy duty central steel core load distribution construction
- US Coast Guard approved inner closed cell rigid urethane buoyancy foam

- Impact absorbing, resilient heat laminated cross-linked polyethylene foam core foam
- Thick, tough filament nylon tire cord reinforced urethane skin

OCEAN GUARD PENDANT BUOYS

BUOY MODEL	BUOYANCY		BUOY		DIAMETER		BUOY		HEIGHT		WORKING	
	NET		WEIGHT		OVERALL		LENGTH		OVERALL		LOAD	
	LBS	KG	LBS	KG	FT	M	FT	M	FT	M	FT	TONS
PB-25	5,511	2,500	1,223	555	4.5	1.4	6.8	2.1	7.3	2.2	150,000	68
PB-50	11,023	5,000	2,123	963	6.0	1.8	7.2	2.2	8.7	2.7	150,000	68
PB-75	16,534	7,500	3,184	1,444	6.5	2.0	9.2	2.8	9.2	2.8	150,000	68
PB-100	22,046	10,000	4,197	1,904	7.0	2.1	11.0	3.4	9.9	3.0	150,000	68
PB-150	33,069	15,000	5,351	2,427	8.0	2.4	12.0	3.7	10.9	3.3	150,000	68
PB-200	44,092	20,000	7,152	3,244	8.6	2.6	13.6	4.1	11.5	3.5	200,000	91
PB-250	55,115	25,000	9,312	4,224	9.4	2.9	13.7	4.2	12.3	3.7	200,000	91
PB-300	66,138	30,000	11,175	5,069	10.0	3.0	14.5	4.4	12.9	3.9	200,000	91
PB-350	77,160	35,000	13,037	5,914	10.3	3.1	16.0	4.9	13.3	4.1	250,000	114
PB-400	88,183	40,000	14,899	6,758	10.4	3.2	18.0	5.5	13.4	4.1	250,000	114